



DOUBLE ROW SELF-ALIGNING BALL BEARING

Available with a parallel or tapered bore



SUFFIX K = TAPERED BORE (1:12 TAPER - NORMALLY USED WITH SEPARATE ADAPTOR SLEEVES)

Bearing No.	Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
	d	D	B	Dyn. C	Stat. C0	
1200	10	30	9	5480	1200	0.034
1201	12	32	10	5550	1250	0.040
1202	15	35	11	7480	1750	0.049
1203	17	40	12	7900	2020	0.073
1204	20	47	14	9950	2650	0.116
1204K	20	47	14	9950	2650	0.116
1205	25	52	15	12000	3300	0.140
1205K	25	52	15	12000	3300	0.140
1206	30	62	16	15800	4700	0.220
1206K	30	62	16	15800	4700	0.220
1207	35	72	17	15800	5080	0.320
1207K	35	72	17	15800	5080	0.320
1208	40	80	18	19200	6400	0.415
1208K	40	80	18	19200	6400	0.415
1209	45	85	19	21800	7320	0.465
1209K	45	85	19	21800	7320	0.465
1210	50	90	20	22800	8080	0.531
1210K	50	90	20	22800	8080	0.531
1211	55	100	21	26800	10000	0.705
1211K	55	100	21	26800	10000	0.705
1212	60	110	22	30200	11500	0.900



DOUBLE ROW SELF-ALIGNING BALL BEARING

Available with a parallel or tapered bore



SUFFIX K = TAPERED BORE (1:12 TAPER - NORMALLY USED WITH SEPARATE ADAPTOR SLEEVES)

Bearing No.	Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
	d	D	B	Dyn. C	Stat. C0	
1212K	60	110	22	30200	11500	0.900
1213	65	120	23	31000	12500	1.150
1213K	65	120	23	31000	12500	1.150
1214	70	125	24	34500	13500	1.240
1214K	70	125	24	34500	13500	1.240
1215	75	130	25	38800	15200	1.390
1215K	75	130	25	38800	15200	1.390
1216	80	140	26	39500	16800	1.700
1216K	80	140	26	39500	16800	1.700
1217	85	150	28	48800	20500	2.060
1217K	85	150	28	48800	20500	2.060
1218	90	160	30	56500	23200	2.590
1218K	90	160	30	56500	23200	2.590
1301	12	37	12	9420	2120	0.067
1302	15	42	13	9500	2280	0.094
1303	17	47	14	12500	3180	0.130
1304	20	52	15	12500	3380	0.165
1305	25	62	17	17800	5050	0.255
1305K	25	62	17	17800	5050	0.255
1306	30	72	19	21500	6280	0.385
1306K	30	72	19	21500	6280	0.385



DOUBLE ROW SELF-ALIGNING BALL BEARING

Available with a parallel or tapered bore



SUFFIX K = TAPERED BORE (1:12 TAPER - NORMALLY USED WITH SEPARATE ADAPTOR SLEEVES)

Bearing No.	Dimensions (mm)			Basic Load Rating (N)		Weight (kg)
	d	D	B	Dyn. C	Stat. C0	
1307	35	80	21	25000	7950	0.510
1307K	35	80	21	25000	7950	0.510
1308	40	90	23	29500	9500	0.715
1308K	40	90	23	29500	9500	0.715
1309	45	100	25	38000	12800	0.955
1309K	45	100	25	38000	12800	0.955
1310	50	110	27	43200	14200	1.200
1310K	50	110	27	43200	14200	1.200
1311	55	120	29	51500	18200	1.600
1311K	55	120	29	51500	18200	1.600
1312	60	130	31	57200	21200	1.950
1312K	60	130	31	57200	21200	1.950
1313	65	140	33	61800	22800	2.420
1313K	65	140	33	61800	22800	2.420
1314	70	150	35	74500	27500	3.000
1314K	70	150	35	74500	27500	3.000
1315	75	160	37	79000	29800	3.550
1315K	75	160	37	79000	29800	3.550
1316	80	170	39	86700	31400	4.170
1316K	80	170	39	86700	31400	4.170
1317K	85	180	41	97800	37800	5.000