



## 30- / 30-- Series Extra Light Series Double Row Angular Contact Ball Bearings



Part Number	Dimensions			Load Rating		Weight (kg)
	d	D	B	Dynamic (N)	Static (N)	
3000 -2RS	10	26	12	5700	3250	0.022
3000 -ZZ	10	26	12	5700	3250	0.022
3001 -2RS	12	28	12	6200	3750	0.025
3001 -ZZ	12	28	12	6200	3750	0.025
3002 -2RS	15	32	13	8600	5400	0.036
3002 -ZZ	15	32	13	8600	5400	0.036
3003 -2RS	17	35	14	9200	6200	0.042
3003 -ZZ	17	35	14	9200	6200	0.042
3004 -2RS	20	42	16	14500	9600	0.080
3004 -ZZ	20	42	16	14500	9600	0.080
3005 -2RS	25	47	16	15500	11100	0.100
3005 -ZZ	25	47	16	15500	11100	0.100
3006 -2RS	30	55	19	20300	15600	0.160
3006 -ZZ	30	55	19	20300	15600	0.160
3007 -2RS	35	62	20	24500	21400	0.200
3007 -ZZ	35	62	20	24500	21400	0.200
3008 -2RS	40	68	21	25500	21700	0.250
3008 -ZZ	40	68	21	25500	21700	0.250

**Suffix guide: 2RS = 2 Rubber Seals / ZZ = 2 Metal Dust Shields**