



**SINGLE ROW
MEDIUM SERIES
SINGLE ROW
ANGULAR CONTACT
BALL BEARINGS 7300
SERIES**



Part Number	Dimensions			Load Rating		Weight (kg)
	d	D	B	Dynamic (N)	Static (N)	
7300B	10	35	11	8950	4150	0.054
7301B	12	37	12	10800	5050	0.065
7302B	15	42	13	12800	6750	0.088
7302B-2RS	15	42	13	12800	6750	0.088
7303B	17	47	14	13800	7300	0.121
7303B-2RS	17	47	14	13800	7300	0.121
7304B	20	52	15	16200	8700	0.156
7304B-2RS	20	52	15	16200	8700	0.156
7305B	25	62	17	22900	13300	0.248
7305B-2RS	25	62	17	22900	13300	0.248
7306B	30	72	19	27600	17400	0.381
7306B-2RS	30	72	19	27600	17400	0.381
7307B	35	80	21	32500	20200	0.512
7307B-2RS	35	80	21	32500	20200	0.512
7308B	40	90	23	39700	25200	0.733
7308B-2RS	40	90	23	39700	25200	0.733
7309B	45	100	25	50600	34100	0.97
7310B	50	110	27	64400	44300	1.23
7311B	55	120	29	74300	52000	1.57
7312B	60	130	31	84900	60300	1.696
7313B	65	140	33	96100	69300	2.38
7314B	70	150	36	108000	78900	2.89
7315B	75	160	37	118000	89200	3.47
7316B	80	170	39	127000	100000	4.13

Cage Materials: Steel / Nylon

Suffix guide: B = 40° Contact Angle / 2RS = 2 Rubber Seals