

Part Number	Alt Reference	Dimensions (mm)			Basic Load Rating (N)		Limiting speed (r/min)		Weight (kg)
							Lubrication		
		Bore	Outer	Width	Dyn. C	Stat. C0	Grease	Oil	
87008	38KVLL2	8	24	10.32/8	3320	1430	23000	-	0.0200
87016	202KLL3	16	35	12.2/11	7610	3750	13000	-	0.0470
87500	200FSF	10	30	12.7/9	5070	2400	17000	-	0.0350
87501	201FSF	12	32	12.7/10	8190	3650	15000	-	0.0410
87502	202FSF	15	35	12.7/12.2	7610	3750	13000	-	0.0500
87503	202FSF	17	40	14.3/12	9560	4800	12000	-	0.0750
87504	204FSF	20	47	15.9/14	13000	6700	10000	-	0.1100
87505	205FSF	25	52	15.9/15	14000	8000	8500	-	0.1300
88501	201FFS/201KLL2	12	32	15.4/10	6760	3050	15000	-	0.0430
88502	202FFS/202KLL2	15	35	14.4/11	7610	3750	13000	-	0.0580
88503	203FFS/203KLL2	17	40	16.6/12	9560	4800	12000	-	0.0820
88504	204FFS/204KLL2	20	47	17.8/14	13000	6700	1000	-	0.1200
88505	205FFS/205KLL2	25	52	16.8/15	14000	8000	8500	-	0.1380
88506	206FFS/206KLL	30	62	24/16	19500	11400	7500	-	0.2600
88507	207FFS/207KLL	35	72	25/17	25500	15300	6300	-	0.3600
88508	208FFS	40	80	27/21	29100	18000	5600	-	0.4800
88509		45	85	27/21	32693	20461	5200	-	0.5500
88510		50	90	30/22	35139	23130	4700	-	0.6250

875-- Series
Extended inner
on one side only



885-- Series
Extended inner
on both sides

