



STAINLESS STEEL RADIAL BALL BEARINGS

SS6000 SERIES



Part Number	Bore Diameter	Outer Diameter	Width	Dynamic Load Rating	Static Load Rating	Limiting Speed Grease	Weight
	mm	mm	mm	C (N)	C0 (N)	r/min	kg
SS6000-2RS	10	26	8	3500	1900	19000	0.019
SS6000-ZZ	10	26	8	3500	1900	29000	0.019
SS6001-2RS	12	28	8	3800	2300	17000	0.021
SS6001-ZZ	12	28	8	3800	2300	26000	0.021
SS6002-2RS	15	32	9	4200	2800	16000	0.030
SS6002-ZZ	15	32	9	4200	2800	22000	0.030
SS6003-2RS	17	35	10	4500	3200	12000	0.039
SS6003-ZZ	17	35	10	4500	3200	20000	0.039
SS6004-2RS	20	42	12	7000	4900	10000	0.069
SS6004-ZZ	20	42	12	7000	4900	18000	0.069
SS6005-2RS	25	47	12	8400	6400	9000	0.080
SS6005-ZZ	25	47	12	8400	6400	15000	0.080
SS6006-2RS	30	55	13	10000	8100	7500	0.116
SS6006-ZZ	30	55	13	10000	8100	13000	0.116
SS6007-2RS	35	62	14	11900	10000	6500	0.155
SS6007-ZZ	35	62	14	11900	10000	12000	0.155
SS6008-2RS	40	68	15	12600	11400	5800	0.190
SS6008-ZZ	40	68	15	12600	11400	10000	0.190
SS6009-2RS	45	75	16	15600	14300	5300	0.240
SS6009-ZZ	45	75	16	15600	14300	9200	0.240
SS6010-2RS	50	80	16	16200	15700	4800	0.260
SS6010-ZZ	50	80	16	16200	15700	8400	0.260
SS6011-2RS	55	90	18	21100	20800	4300	0.390
SS6011-ZZ	55	90	18	21100	20800	7700	0.390
SS6012-2RS	60	95	18	22200	22700	4000	0.410
SS6013-2RS	65	100	18	23000	24500	3700	0.420
SS6014-2RS	70	110	20	28300	30400	3500	0.600
SS6015-2RS	75	115	20	29800	32800	3300	0.678
SS6016-2RS	80	125	22	35600	39200	3100	0.863
SS6017-2RS	85	130	22	37100	42100	2900	0.907
SS6018-2RS	90	140	24	43900	49000	2700	1.160
SS6019-2RS	95	145	24	45400	52900	2500	1.218
SS6020-2RS	100	150	24	47800	52900	2400	1.350