



STAINLESS STEEL RADIAL BALL BEARINGS

SS6300 SERIES



Part Number	Bore Diameter	Outer Diameter	Width	Dynamic Load Rating	Static Load Rating	Limiting Speed Grease	Weight
	mm	mm		C (N)	C0 (N)	r/min	
SS6300-2RS	10	35	11	6000	3300	15000	0.058
SS6300-ZZ	10	35	11	6000	3300	23000	0.058
SS6301-2RS	12	37	12	7300	4100	14000	0.060
SS6301-ZZ	12	37	12	7300	4100	20000	0.060
SS6302-2RS	15	42	13	8600	5300	17000	0.082
SS6302-ZZ	15	42	13	8600	5300	12000	0.082
SS6303-2RS	17	47	14	10100	6400	16000	0.115
SS6303-ZZ	17	47	14	10100	6400	11000	0.115
SS6304-2RS	20	52	15	11900	7600	14000	0.144
SS6304-ZZ	20	52	15	11900	7600	9500	0.144
SS6305-2RS	25	62	17	16900	11400	12000	0.232
SS6305-ZZ	25	62	17	16900	11400	7500	0.232
SS6306-2RS	30	72	19	21100	15700	10000	0.360
SS6306-ZZ	30	72	19	21100	15700	6300	0.360
SS6307-2RS	35	80	21	24900	18600	6000	0.460
SS6307-ZZ	35	80	21	24900	18600	8800	0.460
SS6308-2RS	40	90	23	30800	23500	7800	0.630
SS6308-ZZ	40	90	23	30800	23500	5000	0.630
SS6309-2RS	45	100	25	39500	30900	7000	0.810
SS6309-ZZ	45	100	25	39500	30900	4500	0.810
SS6310-2RS	50	110	27	46400	37200	4300	1.070
SS6310-ZZ	50	110	27	46400	37200	6400	1.070
SS6311-2RS	55	120	29	53600	44100	3800	1.350
SS6312-2RS	60	130	31	61400	51000	3400	2.100
SS6313-2RS	65	140	33	69200	58800	3200	2.100